


- NOTES:
1. ELECTRICAL:
- 1.1 IMPEDANCE: 50Ω
 - 1.2 INSULATION RESISTANCE: 5000MΩ MIN
 - 1.3 FREQUENCY RANGE: DC~40GHz
 - 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
 - 1.5 VSWR ≤ 1.20:1 @ 40GHz
 - 1.6 INSERTION LOSS: 0.3dB
2. ENVIRONMENTAL:
- TEMPERATURE RANGE: -55° to +165°
3. MATERIAL AND FINISH:
- (1) BODY: STAINLESS STEEL, PASSIVATE
 - (2) CENTER CONTACT: BERYLLIUM COPPER, GOLD PLATING
 - (3) DIELECTRIC: PTFE, N/A

3. MATERIAL AND FINISH:

- (1) BODY: STAINLESS STEEL, PASSIVATE
- (2) CENTER CONTACT: BERYLLIUM COPPER, GOLD PLATING
- (3) DIELECTRIC: PTFE, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS



TOLERANCES UNLESS OTHERWISE SPECIFIED:

- 0 P/C ±0.25
- 1 P/C ±0.15
- 2 P/C ±0.12
- 3 P/C ±
- 4 ANGLES ±1°

DMN	DWP	17/12/2018
CHK		
APVD		
PRODUCT SPEC		
APPLICATION SPEC		
WEIGHT		
CUSTOMER DRAWING		

		NAME 2.92mm Female to 2.92mm Female Flange Adapter	
SIZE	TAKE CODE	DRAWING NO	
A4	00779	2.92-KKF	

SEE TABLE

SEE TABLE

CUSTOMER DRAWING

SCALE 2: 1 SHEET 1 OF 1 R/E 1