



NOTES:

- 1.ELECTRICAL:
 - 1.1 IMPEDANCE: 50Ω
 - 1.2 INSULATION RESISTANCE: 5000MΩ MIN
 - 1.3 FREQUENCY RANGE: DC~26.5GHz
 - 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
 - 1.5 VSWR: ≤1.20
- 2.ENVIRONMENTAL:
 - 2.1 TEMPERATURE RANGE: -55° to +165°
 - 2.2 DURABILITY: 500 CYCLES

3.MATERIAL AND FINISH:
 BODY: BRASS, STAINLESS STEEL, PASSIVATE
 NUT: STAINLESS STEEL, PASSIVATE
 CENTER CONTACT: BERYLLIUM COPPER,
 GOLD PLATING
 DIELECTRIC: PEI, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN bob 18/02/2018	ZDeci Microwave	
DIMENSIONS MM	TOLERANCES UNLESS OTHERWISE SPECIFIED.	CHK		
0 PLC ±0.25	1 PLC ±0.15	APVD	2.4mm Male To 3.5mm Female Adaptors	
2 PLC ±0.12	3 PLC ±	PRODUCT SPEC		
4 PLC ±	ANGLES ±1°	APPLICATION SPEC		
MATERIAL	FINISH	WEIGHT	SIZE A3	
SEE TABLE	SEE TABLE	—	CAGE CODE 00779	
		DRAWING NO 2.4/3.5-KJ		
		CUSTOMER DRAWING		
		SCALE 4:1	SHEET 1 OF 1	
		RVE 1		