



NOTES:

- 1.ELECTRICAL:
 - 1.1 IMPEDANCE: 50Ω
 - 1.2 INSULATION RESISTANCE: 5000MΩ MIN
 - 1.3 FREQUENCY RANGE: DC~26.5GHz
 - 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
 - 1.5 VSWR: ≤1.20
- 2.ENVIRONMENTAL:
 - 2.1 TEMPERATURE RANGE: -55° to +165°
 - 2.2 DURABILITY: 500 CYCLES

3.MATERIAL AND FINISH:
 BODY: BRASS, STAINLESS STEEL, PASSIVATE
 NUT: STAINLESS STEEL, PASSIVATE
 CENTER CONTACT: BERYLLIUM COPPER,
 GOLD PLATING
 DIELECTRIC: PEI, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN bob	18/02/2018	ZDecI Microwave	
DIMENSIONS MM	TOLERANCES UNLESS OTHERWISE SPECIFIED.	APVD		NAME	
	0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ±— 4 PLC ±— ANGLES ±1°	PRODUCT SPEC		2.4mm Male To 3.5mm male Adaptors	
MATERIAL	FRESH	APPLICATION SPEC		SIZE	CAGE CODE
SEE TABLE	SEE TABLE			A3	00779
		DRAWING NO		2.4/3.5-JJ	
		CUSTOMER DRAWING		SCALE	SHEET
				4:1	1 OF 1
				R/E	1