


LOC	DIST	P	LTR	DATE	DMN	APVD
—	—	P	—	—	—	—



- NOTES:
- 1.ELECTRICAL:
- 1.1 IMPEDANCE: 50Ω
  - 1.2 INSULATION RESISTANCE:50000MΩ MIN
  - 1.3 FREQUENCY RANGE: DC~4GHz
  - 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
  - 1.5 VSWR≤1.15:1@4GHz
- 2.ENVIROMENTAL:
- 2.1 TEMPERATURE RANGE: -55° to +165°
- 3.MATERIAL AND FINISH:
- 3.1 BODY: BRASS, NICKEL PLATING
  - 3.2 CENTER CONTACT: BERYLLIUM COPPER, GOLD PLATING
  - 3.3 DIELECTRIC: PTFE, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DMN	DWP	17/12/2018	<p>Jiangsu ZDeci Microwave Technology Co., Ltd.</p>
CHK			

DIMENSIONS	TOLERANCES UNLESS OTHERWISE SPECIFIED:	APVD	NAME
MM	0 P/C ±0.25 1 P/C ±0.15 2 P/C ±0.12 3 P/C ± ANGLES 1°	PRODUCT SPEC	N Female TO BNC Male Adapter

MATERIAL	FINISH	APPLICATION SPEC	SIZE	CAGE CODE	DRAWING NO
SEE TABLE	SEE TABLE		A4	00779	N/BNC-KJ

CUSTOMER DRAWING	WEIGHT	SCALE	SHEET	OF	R/E
		2: 1	1	1	1