



Mounting Hole
Dimension

- NOTES:
- ELECTRICAL:
 - IMPEDANCE: 50Ω
 - INSULATION RESISTANCE: 5000MΩ MIN
 - FREQUENCY RANGE: DC~18GHZ
 - DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
 - VSWR ≤ 1.20:1 @ 18GHZ
 - INSERTION LOSS: 0.2 dB

- ENVIRONMENTAL:
 - TEMPERATURE RANGE: -55° to +165°

- MATERIAL AND FINISH:
 - BODY: STAINLESS STEEL, PASSIVATE
 - CENTER CONTACT: BERYLLIUM COPPER, GOLD PLATING
 - DIELECTRIC: PTFE, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS
MM



TOLERANCES UNLESS OTHERWISE SPECIFIED:

- 0 P/C ±0.25
- 1 P/C ±0.15
- 2 P/C ±0.12
- 3 P/C ±
- 4 ANGLES 1°

MATERIAL SEE TABLE

FINISH SEE TABLE



Jiangsu Zdecl Microwave Technology Co., Ltd.

NAME

N Female To SMA Female Adaptor

SIZE A4

DWG CODE 00779

DRAWING NO N/SMA-KKY-01

DMN	DWP	17/12/2018
CHK		
APVD	PRODUCT SPEC	
	APPLICATION SPEC	
	WEIGHT	
	CUSTOMER DRAWING	

SCALE	2: 1	SHEET	1	OF	1	R/E	1
-------	------	-------	---	----	---	-----	---