



NOTES:

1. ELECTRICAL:
- 1.1 IMPEDANCE: 50Ω
  - 1.2 INSULATION RESISTANCE: 5000MΩ MIN
  - 1.3 FREQUENCY RANGE: DC~11GHz
  - 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 750V MAX AT SEA LEVEL
  - 1.5 VSWR≤1.20:1@11GHz
  - 1.6 INSERTION LOSS: 0.2dB

2. ENVIRONMENTAL:

- 2.1 TEMPERATURE RANGE: -55° to +165°

3. MATERIAL AND FINISH:

- 3.1 BODY: STAINLESS STEEL, PASSIVATE
- 3.2 CENTER CONTACT: BERYLLIUM COPPER, GOLD PLATING
- 3.3 DIELECTRIC: PTFE, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.

DMN	DWP	17/12/2018	<p>Jiangsu Zdeci Microwave Technology Co., Ltd.</p>
CHK			
DIMENSIONS		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
MM	0 P/C	±0.25	APVD
	1 P/C	±0.15	PRODUCT SPEC
	2 P/C	±0.12	APPLICATION SPEC
	3 P/C	±	WEIGHT
	ANGLES	±1°	CUSTOMER DRAWING
FINISH		NAME	
SEE TABLE		TNC Female To SMA Female Adaptor	
MATERIAL		SIZE	TAGE CODE
SEE TABLE		A4	00779
		DRAWING NO	TNC/SMA-KK
		SCALE	2: 1
		SHEET	1 OF 1
		R/E	1